

- SAM (Simple Attenuation Model), 3-2, 3-58
- Sand attenuation, 6-73
- Satellites
 - ACTS, 7-18, 7-24, 7-78, 7-117
 - ATDRSS, 7-35
 - ATS-5, 5-21
 - ATS-6, 4-40, 5-3, 5-4, 5-22
 - BS, 5-3, 5-4
 - COMSTAR, 4-40, 5-4, 5-22, 5-28, 5-29, 5-36, 5-39
 - CS, 5-3, 5-4, 5-24
 - CTS, 4-40, 5-4, 5-8
 - DSCS III, 7-30
 - ECS, 5-3, 5-4
 - ETS-II, 5-3, 5-4, 5-19, 5-24, 5-35
 - FLTSATCOM, 7-30
 - INTELSAT-VI, 7-19, 7-29
 - ITALSAT, 7-33
 - OTS, 5-3, 5-4, 5-18, 5-20
 - SIRIO, 4-40, 5-3, 5-4, 5-18, 5-19, 5-20
- Saturated partial pressure, 6-16
- Scintillation
 - amplitude, 6-76, 6-101
 - distribution function, 6-95
 - phase, 6-90, 6-103
- Signal diversity, 7-111
- SIRIO satellite, 4-40, 5-3, 5-4, 5-18, 5-19, 5-20
- Site diversity
 - analytical model, 7-102, 7-107
 - baseline orientation, 7-90
 - definition, 7-80
 - design factors, 7-88
 - elevation angle, 7-90
 - empirical model, 7-93
 - experiments summary, 7-86
 - extended empirical model, 7-95
 - frequency dependence, 7-91
 - interstation link, 7-92
 - local climatology, 7-92
 - multiple earth terminals, 7-93
 - path azimuth angle, 7-90
 - rain cell anisotropy, 7-91
 - separation distance, 7-88
 - switching rates, 7-92
- Sky noise, 1-4, 6-130
 - clear-air, 6-131
 - clouds, 6-139
 - computation of multiple contributors, 6-140
 - dust, 6-139
 - extraterrestrial sources, 6-140
 - fog, 6-139
 - lunar, 6-142

- radio stars, 6-142
- rain, 1-6, 6-136
- sample calculations, 6-136
- sand, 6-139
- solar, 6-140
- uplink, 6-143
- Sky noise temperature, 1-6
- Space diversity, 7-83
- Specific attenuation
 - dry air, 6-13
 - rain, 2-7, 2-11
 - frequency dependence, 2-11
 - rain rate dependence, 2-11, 2-14
 - regression values, 2-12, 2-14, 6-40
 - water droplets, 6-62
 - water vapor, 6-62
- Storm Data Report, 2-17
- SS/TDMA 7-17, 7-32
- System design
 - availability allocation, 7-37, 7-73
 - clear-air absorption, 7-63
 - composite carrier-to-noise ratio, 7-48, 7-71
 - depolarization analysis, 7-58
 - initial phase, 7-43
 - overview of procedure, 7-1
 - phases, 7-40
 - power budget, 7-50
 - sample calculation, 7-64
 - process, 7-3, 7-41
 - propagation analysis, 7-42, 7-55, 7-63
 - rain margin, 7-55
 - synthesis phase, 7-46
 - sample calculation, 7-52
- System performance criteria
 - analog, 7-12
 - bit error rate, 7-9
 - CCIR, 7-9
 - DCA, 7-9
 - digital, 7-9
 - examples, 7-43
 - overview summary, 7-7
- T-
- TDMA (time division multiple access), 6-5, 7-17, 7-21, 7-117
 - satellite switched (SS), 7-17, 7-32
- Telecommunications services, 6-4
- Throughput, 7-11
- Transmission coefficient, 4-25
- Tropospheric delays, 6-5
- Two-component rain attenuation model, 3-2, 3-39
- U-
- Uplink Noise, 6-143

-V-

Volume cell rainfall, 3-41

VSAT, 7-23

-W-

Wave antenna interaction, 4-8

Water vapor

 and relative humidity, 6-16

 definition, 6-16

 density, 6-14

 specific attenuation, 6-13

Worst month statistics, 6-59

-X-

XPD (see: Crosspolarization discrimination)

XPI (see: Crosspolarization isolation)

-Z-

Zero degree isotherm, 2-4, 3-26, 3-38, 6-23

Report Documentation Page

| | | | | | |
|---|--|--|--|--|--|
| 1. Report No. NASA RP-1082(04) | | 2. Government Accession No. | | 3. Recipient's Catalog No. | |
| 4. Title and Subtitle Propagation Effects Handbook for Satellite Systems Design - A Summary of Propagation Impairments on 10 to 100 GHz Satellite Links With Techniques for System Design | | | | 5. Report Date February 1989 | |
| | | | | 6. Performing Organization Code | |
| 7. Author(s) Louis J. Ippolito | | | | 8. Performing Organization Report No. | |
| | | | | 10. Work Unit No. | |
| 9. Performing Organization Name and Address Westinghouse Electric Corporation Friendship Site Box 1897 Baltimore, MD 21203 | | | | 11. Contract or Grant No. NAS7-100;958178(JPL) | |
| | | | | 13. Type of Report and Period Covered Reference Publication (Fourth Edition) | |
| 12. Sponsoring Agency Name and Address National Aeronautics and Space Administration Washington, DC 20546 Office of Space Science and Applications | | | | 14. Sponsoring Agency Code | |
| | | | | | |
| 15. Supplementary Notes | | | | | |
| 16. Abstract The NASA Propagation Effects Handbook for Satellite Systems Design provides a systematic compilation of the major propagation effects experienced on space-Earth paths in the 10 to 100 GHz frequency band region. It provides both a detailed description of the propagation phenomena and a summary of the impact of the effect on communications system design and performance. Chapters II through V describe the propagation effects, prediction models, and available experimental data bases. In Chapter VI, design techniques and prediction methods available for evaluating propagation effects on space-Earth communications systems are presented. Chapter VII addresses the system design process and how the effects of propagation on system design and performance should be considered and how they can be mitigated. Examples of operational and planned K_u , K_a , and EHF satellite communications systems are given. | | | | | |
| 17. Key Words (Suggested by Author(s)) Microwave Propagation, Rain Attenuation, Satellite Communications Systems, K_u , K_a , EHF Propagation, Radio Noise | | | | 18. Distribution Statement Unclassified - Unlimited Subject Category 32 | |
| 19. Security Classif. (of this report) Unclassified | | 20. Security Classif. (of this page) Unclassified | | 21. No. of pages 536 | |
| | | | | 22. Price A23 | |